



## Print your medical imaging in HD colour with integrated DICOM A4 printers

OKI is a leader in printing innovation, providing organisations with High Definition colour printing devices based on digital LED technology, and now our sophisticated range of printers integrate seamlessly with your clinical systems using DICOM.

### A first in medical imaging and printing

This is a first in digital printer technology, combining the cost effectiveness and high quality output of an LED printer with embedded DICOM software, allowing you to print directly from medical equipment without the use of conversion software or external print servers. You no longer need to settle for expensive printing on specialist media and devices.

With the C610 DM you can now print your medical imaging cost effectively on standard media formats in vibrant, HD colour and in sizes up to A4. From nuclear medicine (2D Scintigraphy and 3D SPECT tomography) to ultrasounds, these images can now be easily printed for your own non-diagnostic use or to provide a copy for your patients and clients to take away with them.

### Reduce your costs and improve your printing

The C610 DM is not only perfect for your medical imaging printing, it can also be used for your standard office printing, from patient letters and forms to medical reports, allowing you to choose one machine that answers all the needs of your organisation, cutting down on the number of devices and consumables used.

The C610 DM is based on our existing, award winning printers, offering the same reliability, ease of use, low total cost of ownership, media flexibility and high quality output, with the additional benefit of embedded DICOM technology.

Through system integration, the use of energy efficient equipment, standard printer consumables, the C610 DM offers considerable savings for your day-to-day printing needs.

### See it clearer with OKI

Talking directly with your medical imaging equipment, the C610 DM presents many opportunities for printing high quality, non-diagnostic images in HD mono and colour on a wide range of media. The significantly reduced costs of printing using the C610 DM, compared with traditional DICOM printing technologies, allows medical establishments to change their approach to printing.

Imagine the possibilities; offer mothers-to-be A4 ultrasound scans or keep sharp and clear non-diagnostic images in patients' records, and all at a very low cost. In fact, the same cost of printing as standard office documents.

### Benefits at a Glance

- Fully integrated DICOM print server
- Up to 2 simultaneous imaging equipment connections
- Recommended usage - Nuclear medicine, ultrasound
- High quality non-diagnostic mono and colour printing of medical images
- No additional external hardware or software required
- Handles media from A6 to A4 wide 1200mm banners, from 64 to 250gsm



# C610 DM - Colour and Mono Printer

PRINTER	
Print speed	A4: 34ppm colour, 36ppm mono
Time to first print	9 seconds colour, 8 seconds mono
Warm up time	up to 60 seconds from power on & up to 35 seconds from power save
Processor speed	533MHz
PRINT QUALITY	
Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi, 600 x 600dpi
Enhancements	Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers)
INTERFACE AND SOFTWARE	
Connectivity	Hi-Speed USB, 10/100-TX Ethernet
DICOM server	Print SCP 3.0, 2 simultaneous printing connections, Unlimited number of AE Title providing their own parameter set, Recommended usage for ultrasound and nuclear medicine, A4 paper format
Printer languages	PCL 6 (XL3.0) and PCL5c, PostScript 3 (emulation), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.7, XPS
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNT, WSDPrint, JetDirect protocols. NetBIOSoverTCP, NetWare 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. AppleTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other: EAP, DICOM Print 3.0
OS Compatibility <sup>1</sup>	Windows 2000 / XP Home / XP Professional (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Vista (32-bit & 64-bit) / 7 (32-bit & 64-bit); Mac OS X 10.3.9 - 10.7
Advanced networking and security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encryption, Secure Print, Secure Erase, Data encryption, MAC filtering, IP filtering, IPsec
Utility Suite <sup>1</sup>	Color Correct, OKI LPR <sup>2</sup> , PrintSuperVision.net <sup>2</sup> , Swatch Utility, Template Manager <sup>2</sup> , Web Driver Installer <sup>2</sup> , Print Control Server <sup>2</sup> , Print Control Client, Storage Device Manager <sup>2</sup> , Gamma Utility, Profile Assistant, Colour Access Policy Manger <sup>2</sup>
PAPER HANDLING	
Paper capacity	Tray 1: 300 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm
Maximum paper capacity	1,460 sheets of 80gsm
Paper sizes	Tray 1: A4, A5, B5, A6; Tray 2/3: A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6, 10 Envelopes (Com-9, Com-10, DL, Monarch, C5), Labels (Avery 7162, 7664, 7666), Custom Size: up to 1,200mm length banners; Duplex: A4, A5, B5, Custom Size: Width 148-215.9mm x Length 210-355.6mm
Paper weight	Tray 1/2/3: 64 to 220gsm; Multi-purpose tray: 64 to 250gsm; Duplex: 64 to 120gsm
Duplex	Optional
Paper output	250 sheets face down, 100 sheets face up, 80gsm

<sup>1</sup> Check local OKI website for latest driver releases and OS compatibility; <sup>2</sup> Windows only; <sup>3</sup> Including all consumables

**Consumables Information:** For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

TYPEFACES	
Printer fonts	Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts. OCR-A/B; USPS ZIP Barcode
Barcode	Barcode with Checksum support

GENERAL FEATURES	
Memory	Standard RAM: 768MB
Environment	Operating temperature/humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
	Storage temperature/humidity: -10°C to 43°C, 10% to 90% RH
Power supply	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Power consumption	Typical: 600W; Max: 1300W; Idle: 100W; Power Save: <15W; Sleep: 1.2W
Noise level	Operating: 54dB(A); Standby: 37dB(A); Power save: Background Level
Dimensions (HxWxD)	340 x 435 x 546mm
Weight <sup>3</sup>	26kg
Duty cycle	Recommended usage: up to 600 pages/month for DICOM printing
Warranty	1 year
Product order number	C610 DM: 45079301

ACCESSORIES (ORDER NUMBERS)	
2nd paper tray	44274502
3rd paper tray	44274502
Duplex	01272601
Cabinet	01219302

CONSUMABLES (ORDER NUMBERS)	
Toner cartridges* (6,000 pages)	Cyan: 44315307; Magenta: 44315306; Yellow: 44315305
Toner cartridges* (8,000 pages)	Black: 44315308
Image drum** (20,000 pages)	Cyan: 44315107; Magenta: 44315106; Yellow: 44315105; Black: 44315108
Transfer Belt (60,000 pages)	44341902
Fuser Unit (60,000 pages)	44289103

\*Toner: A4 pages yield compliant with ISO/IEC 19798. Printer shipped with 2,000 A4 pages.  
\*\*Drum: A4 pages average life.

**OkI Systems (Polska) Sp. z o.o.**

Domaniewska str. 42  
02-672 Warsaw  
Tel.: +48 (22) 448 65 00  
Fax: +48 (22) 448 65 01

[www.oki.pl](http://www.oki.pl)

